


FEATURES AND BENEFITS

Product Summary		
I_{FM}	200mA	@25 °C
V_F	0.24V	@0.1mA
V_{RRM}	30V	@25 °C

- For High-Speed Switching Applications
- Low Current Leakage
- RoHS Compliant / Green EMC UL Flammability Classification Rating 94V-0
- Matte Tin (Sn) Lead finish Solderable per MIL-STD-202, Method 208
- Moisture Sensitivity: Level 1 per J-STD-020

SOT-723



Maximum Ratings (TA = 25 °C unless otherwise noted)			
PARAMETER	SYMBOL	VALUE	UNIT
Repetitive Peak Reverse Voltage	V_{RRM}	30	V
Working Reverse Voltage	V_{RWM}	30	V
RMS Reverse Voltage	$V_{R(RMS)}$	21	V
Forward Continuous Current	I_{FM}	200	mA
Non-Repetitive Peak Forward Surge Current (@ t = 8.3ms)	I_{FSM}	600	mA
Power Dissipation	P_{TM}	150	mW
Junction Temperature	T_J	125	°C
Storage Temperature	T_{STG}	-55 to +150	°C





THERMAL CHARACTERISTICS (TA = 25 °C unless otherwise noted)			
PARAMETER	SYMBOL	VALUE	UNIT
Thermal Resistance from Junction to Ambient*	$R_{\theta JA}$	667	°C/W

* Device mounted on 1"x1" FR4 PCB

ELECTRICAL CHARACTERISTICS (TA = 25 °C unless otherwise noted)


PARAMETER	SYMBOL	CONDITION	MIN	MAX	UNIT
Forward Voltage	V_F	$I_F = 0.1\text{mA}$		0.24	V
		$I_F = 1\text{mA}$		0.32	
		$I_F = 10\text{mA}$		0.40	
		$I_F = 30\text{mA}$		0.50	
		$I_F = 100\text{mA}$		1.00	
Reverse Current	I_R	$V_R = 25\text{V}$		2.0	μA
Capacitance	C_T	$V_R = 1.0\text{V}, f = 1\text{MHz}$		10	pF
Reverse Recovery Time	t_{rr}	$I_F = 10\text{mA}, I_R = 10\text{mA}, I_{R(\text{REC})} = 1\text{mA}$		5.0	ns

RATING AND CHARACTERISTICS CURVES




PACKAGE OUTLINE DIMENSIONS

SOT-723




SUGGESTED PAD LAYOUT



DEVICE MARKING AND ORDERING INFORMATION

DEVICE	Marking	Quantity	Packing
BAT54CM	KL3	8000/7"Reel	Tape & Reel



XXX: Product Marking Code

Σ : Date Code (Rotate 90° counterclockwise)

Odd Year	Even Year
1	E
2	F
3	H
4	J
5	K
6	L
7	N
8	P
9	U
T	X
V	Y
C	Z

NOTICE:

AZUREMOTO'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS COMPONENTS IN ANY LIFE SUPPORT DEVICES OR SYSTEMS. AZUREMOTO RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY OR RUGGEDNESS.