


FEATURES AND BENEFITS

Product Summary		
I_{FM}	225mA	@25 °C
V_F	0.87V	@20mA
V_{RRM}	350V	@25 °C

- For General Purpose Switching Applications
- High Conductance
- RoHS Compliant / Green EMC UL Flammability Classification Rating 94V-0
- Matte Tin (Sn) Lead finish Solderable per MIL-STD-202, Method 208
- Moisture Sensitivity: Level 1 per J-STD-020
- Weight: 0.01 grams (Approximate)

SOD-123



Cathode  Anode




Maximum Ratings (TA = 25 °C unless otherwise noted)				
PARAMETER		SYMBOL	VALUE	UNIT
Repetitive Peak Reverse Voltage		V_{RRM}	350	V
Working Reverse Voltage		V_{RWM}	350	V
RMS Reverse Voltage		$V_{R(RMS)}$	300	V
Forward Continuous Current		I_{FM}	225	mA
Non-Repetitive Peak Forward Surge Current	(@t=1.0us)	I_{FSM}	4.0	A
	(@t=1.0s)		1.0	A
Power Dissipation		P_{TM}	400	mW
Junction Temperature		T_J	150	°C
Storage Temperature		T_{STG}	-55 to +150	°C

THERMAL CHARACTERISTICS (TA = 25 °C unless otherwise noted)			
PARAMETER	SYMBOL	VALUE	UNIT
Thermal Resistance from Junction to Ambient*	$R_{\theta JA}$	305	°C/W

* Device mounted on 1"x1" FR4 PCB


ELECTRICAL CHARACTERISTICS (TA = 25 °C unless otherwise noted)					
PARAMETER	SYMBOL	CONDITION	MIN	MAX	UNIT
Reverse Breakdown Voltage	V_R	$I_R = 150\mu A$	350		V
Forward Voltage	V_F	$I_F = 20mA$		0.87	V
		$I_F = 100mA$		1.00	
		$I_F = 200mA$		1.25	
Reverse Current	I_R	$V_R = 240V (25^\circ C)$		100	nA
		$V_R = 240V (150^\circ C)$		100	μA
Capacitance	C_T	$V_R = 0V, f = 1MHz$		5.0	pF
Reverse Recovery Time	t_{rr}	$I_F = I_R = 30mA,$ $I_{rr} = 0.1 \cdot I_R, R_L = 100\Omega$		50	ns

RATING AND CHARACTERISTICS CURVES




PACKAGE OUTLINE DIMENSIONS

SOD-123



Symbol	MIN	MAX
A	1.05	1.25
A1	0.00	0.10
A2	1.05	1.15
b	0.45	0.65
c	0.08	0.15
D	1.50	1.70
E	2.60	2.80
E1	3.55	3.85
L	0.500REF	
L1	0.25	0.45
θ	0°	8°
Unit: mm		


SUGGESTED PAD LAYOUT



Symbol	Typ
Q1	3.24
Q	1.0
p	0.8
Unit: mm	

DEVICE MARKING CODE AND ORDERING INFORMATION

DEVICE	Marking	Quantity	Packing
BAV3004W	4P	3000/7"Reel	Tape & Reel



XXX: Product Marking Code

Σ : Date Code (Rotate 90° counterclockwise)

Odd Year	Even Year
1	E
2	F
3	H
4	J
5	K
6	L
7	N
8	P
9	U
T	X
V	Y
C	Z

NOTICE:

AZUREMOTO'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS COMPONENTS IN ANY LIFE SUPPORT DEVICES OR SYSTEMS.

AZUREMOTO RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY OR RUGGEDNESS.