



FEATURES AND BENEFITS

Product Summary		
I_O	150mA	@25 °C
V_F	0.715V	@1mA
V_R	75V	@25 °C

- For General Purpose Switching Applications
- High Conductance
- RoHS Compliant / Green EMC UL Flammability Classification Rating 94V-0
- Matte Tin (Sn) Lead finish Solderable per MIL-STD-202, Method 208
- Moisture Sensitivity: Level 1 per J-STD-020

SOT-363







Maximum Ratings (TA = 25 °C unless otherwise noted)			
PARAMETER	SYMBOL	VALUE	UNIT
Repetitive Peak Reverse Voltage	V_{RRM}	75	V
Working Reverse Voltage	V_{RWM}	75	V
Continuous Forward Current	I_O	150	mA
Non-Repetitive Peak Forward Surge Current (@t=8.3ms)	I_{FSM}	2.0	A
Power Dissipation	P_{TM}	200	mW
Junction Temperature	T_J	150	°C
Storage Temperature	T_{STG}	-55 to +150	°C

THERMAL CHARACTERISTICS (TA = 25 °C unless otherwise noted)			
PARAMETER	SYMBOL	VALUE	UNIT
Thermal Resistance from Junction to Ambient*	$R_{\theta JA}$	625	°C/W

* Device mounted on 1"x1" FR4 PCB




ELECTRICAL CHARACTERISTICS (TA = 25 °C unless otherwise noted)					
PARAMETER	SYMBOL	CONDITION	MIN	MAX	UNIT
Reverse Breakdown Voltage	V_R	$I_R=100\mu A$	75		V
Forward Voltage	V_F	$I_F = 1.0mA$		0.715	V
		$I_F = 10mA$		0.855	V
		$I_F = 50mA$		1.00	V
		$I_F = 150mA$		1.25	V
Reverse Current	I_R	$V_R= 20V$		0.025	μA
		$V_R= 75V$		2.5	μA
Capacitance	C_T	$V_R = 0V, f = 1MHz$		2.00	pF
Reverse Recovery Time	t_{rr}	$I_F=I_R=10mA, I_{rr}=0.1 \cdot I_R, R_L=100\Omega$		4.00	ns

RATING AND CHARACTERISTICS CURVES




PACKAGE OUTLINE DIMENSIONS

SOT-363



Symbol	MIN	MAX
A	0.90	1.00
A1	0.00	0.10
A2	0.90	1.00
b	0.15	0.35
c	0.10	0.15
D	2.00	2.20
E	1.15	1.35
E1	2.15	2.40
e	0.650TYP.	
e1	1.20	1.40
L	0.525REF.	
L1	0.26	0.46
θ	0°	8°
Unit: mm		


SUGGESTED PAD LAYOUT



Symbol	Type
P	0.65
P1	1.94
Q	0.40
S	0.816
Unit: mm	

DEVICE MARKING CODE AND ORDERING INFORMATION

DEVICE	Marking	Quantity	Packing
BAV99DW	KJG	3000/7"Reel	Tape & Reel



XXX: Product Marking Code

Σ : Date Code (Rotate 90° counterclockwise)

Odd Year	Even Year
1	E
2	F
3	H
4	J
5	K
6	L
7	N
8	P
9	U
T	X
V	Y
C	Z

NOTICE:

AZUREMOTO'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS COMPONENTS IN ANY LIFE SUPPORT DEVICES OR SYSTEMS. AZUREMOTO RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY OR RUGGEDNESS.