


FEATURES AND BENEFITS

Product Summary		
I_{FM}	150mA	@25 °C
V_F	0.855V	@10mA
V_{RRM}	100V	@25 °C

- For General Purpose Switching Applications
- High Conductance
- RoHS Compliant / Green EMC UL Flammability Classification Rating 94V-0
- Matte Tin (Sn) Lead finish Solderable per MIL-STD-202, Method 208
- Moisture Sensitivity: Level 1 per J-STD-020
- Weight: 0.006 grams (Approximate)

SOT-323







Maximum Ratings (TA = 25 °C unless otherwise noted)			
PARAMETER	SYMBOL	VALUE	UNIT
Repetitive Peak Reverse Voltage	V_{RRM}	100	V
Working Reverse Voltage	V_{RWM}	75	V
Forward Continuous Current	I_{FM}	150	mA
Non-Repetitive Peak Forward Surge Current (8.3 ms single half sinewave)	I_{FSM}	2.0	A
Power Dissipation	P_{TM}	200	mW
Junction Temperature	T_J	150	°C
Storage Temperature	T_{STG}	-55 to +150	°C

THERMAL CHARACTERISTICS (TA = 25 °C unless otherwise noted)			
PARAMETER	SYMBOL	VALUE	UNIT
Thermal Resistance from Junction to Ambient*	$R_{\theta JA}$	625	°C/W

* Device mounted on 1"x1" FR4 PCB


ELECTRICAL CHARACTERISTICS (TA = 25 °C unless otherwise noted)					
PARAMETER	SYMBOL	CONDITION	MIN	MAX	UNIT
Forward Voltage	V _F	I _F = 1mA		0.715	V
		I _F = 10mA		0.855	
		I _F = 50mA		1.00	
		I _F = 150mA		1.25	
Reverse Current	I _R	V _R = 75V		2.5	μA
Capacitance	C _T	V _R = 0V, f = 1MHz		2.0	pF
Reverse Recovery Time	t _{rr}	I _F = 10mA, I _R = 10mA, I _{rr} = 0.1I _R , R _L = 100ohm		4.0	ns

RATING AND CHARACTERISTICS CURVES




PACKAGE OUTLINE DIMENSIONS

SOT-323



Symbol	MIN	MAX
A	0.90	1.00
A1	0.00	0.10
A2	0.90	1.00
b	0.20	0.40
c	0.08	0.15
D	2.00	2.20
E	2.15	2.45
E1	1.15	1.35
e	1.20	1.40
e1	0.65TYP	
L	0.525REF	
L1	0.26	0.46
e	0°	8°
Unit: mm		

SUGGESTED PAD LAYOUT




Land Pattern Recommendation

Symbol	Type
Q1	2.2
Q	1.3
p	0.5
p1	0.8
Unit: mm	

DEVICE MARKING AND ORDERING INFORMATION

DEVICE	Marking	Quantity	Packing
BAV99W	KJG	3000/7"Reel	Tape & Reel



XXX: Product Marking Code

Σ : Date Code (Rotate 90° counterclockwise)

Odd Year	Even Year
1	E
2	F
3	H
4	J
5	K
6	L
7	N
8	P
9	U
T	X
V	Y
C	Z

NOTICE:

AZUREMOTO'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS COMPONENTS IN ANY LIFE SUPPORT DEVICES OR SYSTEMS.

AZUREMOTO RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY OR RUGGEDNESS.