


FEATURES AND BENEFITS

Product Summary		
I_C	100mA	@25 °C
BV_{CBO}	30V	@ $I_C=10\mu A$
BV_{CEO}	30V	@ $I_C=10mA$
BV_{EBO}	5V	@ $I_E=1\mu A$

- For General Purpose NPN Amplifier
- Low Current Leakage
- RoHS Compliant / Green EMC UL Flammability Classification Rating 94V-0
- Matte Tin (Sn) Lead finish Solderable per MIL-STD-202, Method 208
- Moisture Sensitivity: Level 1 per J-STD-020
- Weight: 0.006 grams (Approximate)

SOT-323









Maximum Ratings (TA = 25 °C unless otherwise noted)			
PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	V_{CBO}	30	V
Collector-Emitter Voltage	V_{CEO}	30	V
Emitter-Base Voltage	V_{EBO}	5	V
Collector Current	I_C	100	mA
Collector Power Dissipation	P_T	150	mW
Junction Temperature	T_J	150	°C
Storage Temperature	T_{STG}	-55 to +150	°C


THERMAL CHARACTERISTICS (TA = 25 °C unless otherwise noted)			
PARAMETER	SYMBOL	VALUE	UNIT
Thermal Resistance from Junction to Ambient*	$R_{\theta JA}$	833	°C/W

* Device mounted on 1"x1" FR4 PCB


ELECTRICAL CHARACTERISTICS (TA = 25 °C unless otherwise noted)					
PARAMETER	SYMBOL	CONDITION	MIN	MAX	UNIT
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 10mA, I_B = 0$	30		V
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = 10\mu A, I_E = 0$	30		V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 1\mu A, I_C = 0$	5		V
Collector Cutoff Current	I_{CBO}	$V_{CB} = 30V, I_E = 0$		15	nA
Emitter Cutoff Current	I_{EBO}	$V_{EB} = 5V, I_C = 0$		0.1	uA
DC Current Gain	h_{FE}	$V_{CE} = 5V, I_C = 2mA$	200	450	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 10mA, I_B = 0.5mA$		0.25	V
		$I_C = 100mA, I_B = 5mA$		0.60	
Base-Emitter Voltage	$V_{BE(on)}$	$V_{CE} = 5V, I_C = 2mA$	0.58	0.7	V
		$V_{CE} = 5V, I_C = 10mA$		0.77	
Transition Frequency	f_T	$V_{CE} = 5V, I_C = 10mA, f = 100MHz$	100		MHz
Output Capacitance	C_{obo}	$V_{CB} = 10V, f = 1MHz$		4.5	pF

RATING AND CHARACTERISTICS CURVES






Transition Frequency (f_T) vs Collector Current (I_C)



Capacitance vs. Reverse Voltage


PACKAGE OUTLINE DIMENSIONS

SOT-323



Symbol	MIN	MAX
A	0.90	1.00
A1	0.00	0.10
A2	0.90	1.00
b	0.20	0.40
c	0.08	0.15
D	2.00	2.20
E	1.15	1.35
E1	2.15	2.45
e	0.65TYP	
e1	1.20	1.40
L	0.525REF	
L1	0.26	0.46
⊘	0°	8°
Unit: mm		

SUGGESTED PAD LAYOUT



Land Pattern Recommendation

Symbol	Type
Q1	2.2
Q	1.3
p	0.5
p1	0.8
Unit: mm	

DEVICE MARKING AND ORDERING INFORMATION

DEVICE	Marking	Quantity	Packing
BC848BW	1K	3000/7"Reel	Tape & Reel

NOTICE:

AZUREMOTO'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS COMPONENTS IN ANY LIFE SUPPORT DEVICES OR SYSTEMS.
AZUREMOTO RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE
RELIABILITY OR RUGGEDNESS.