



FEATURES AND BENEFITS

Product Summary

V_{RRM}	1000V	@25 °C
I_F	10.0A	@25 °C
V_F	1.3V	@ $I_F=5.0A$
I_R	5.0uA	@25 °C

- Glass passivated die construction
- Low reverse leakage
- High surge current capability
- RoHS Compliant / Green EMC UL Flammability Classification Rating 94V-0
- Matte Tin (Sn) Lead finish Solderable per MIL-STD-202, Method 208
- Weight: 1.38 grams (Approximate)

GBP



Maximum Ratings (TA = 25 °C unless otherwise noted)

PARAMETER	SYMBOL	GBP 10T02	GBP 10T04	GBP 10T06	GBP 10T08	GBP 10T10	UNIT
Peak Repetitive Reverse Voltage	V_{RRM}	200	400	600	800	1000	V
DC Blocking Voltage	V_{DC}	200	400	600	800	1000	V
RMS Reverse Voltage	V_{RMS}	140	280	420	560	700	V
Average Rectified Output Current	$I_{F(AV)}$	10.0					A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	200					A
I^2t Rating for Fusing ($t < 8.3ms$)	I^2t	166					A ² s
Operating and Storage Temperature Range	T_J, T_{STG}	-55 to +150					°C

THERMAL CHARACTERISTICS (TA = 25 °C unless otherwise noted)

PARAMETER	SYMBOL	VALUE	UNIT
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	55.0	°C/W

ELECTRICAL CHARACTERISTICS (TA = 25 °C unless otherwise noted)

PARAMETER	SYMBOL	GBP 10T02	GBP 10T04	GBP 10T06	GBP 10T08	GBP 10T10	UNIT
Forward Voltage I _F =5.0A	V _F	1.30					V
Peak Reverse Current @T _A =25°C	I _R	5.0					uA
At Rated DC Blocking Voltage @T _A =125°C		500					
Reverse Recovery Time (Note 1)	t _{rr}	150		250	500		ns

Note:

- Reverse Recovery Test Conditions: IF=0.5A, IR=1.0A, IRR=0.25A

RATING AND CHARACTERISTICS CURVES

FIG. 1- DERATING CURVE OUTPUT RECTIFIED CURRENT




FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT PER LEG




FIG. 3-TYPICAL FORWARD VOLTAGE CHARACTERISTICS






FIG. 4-TYPICAL REVERSE LEAKAGE CHARACTERISTICS



PACKAGE OUTLINE DIMENSIONS


GBP



Symbol	MIN	MAX
A	3.30	3.60
A1	1.80	2.40
D	14.20	14.70
E	10.20	10.60
E1	13.80	14.40
F	1.80	2.20
G	3.71	3.91
H	6.65	7.25
J	1.22	1.42
J1	0.76	0.86
P	3.0Φ	3.4Φ
T	0.30	0.55
Unit: mm		

DEVICE MARKING CODE AND ORDERING INFORMATION

DEVICE	Marking	Quantity	Packing
GBP10T02	GBP10T02	35	Tube
GBP10T04	GBP10T04	35	Tube
GBP10T06	GBP10T06	35	Tube
GBP10T08	GBP10T08	35	Tube
GBP10T10	GBP10T10	35	Tube



Y: Last digit of year (5 for 2025)

M: Manufacture's code

WW: Week code (01 to 53)

GBPXXXX: Device marking code

NOTICE:

AZUREMOTO'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS COMPONENTS IN ANY LIFE SUPPORT DEVICES OR SYSTEMS. AZUREMOTO RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY OR RUGGEDNESS.